
BUICK 2000 Century

S P E C I F I C A T I O N S



3100 SFI V-6



| | 3100 SFI V-6 | |
|--|-----------------------------------|--|
| Туре | 60° V-6 | |
| Bore and Stroke (in.) | 3.51 x 3.31 | |
| Piston Displacement (cu. in.) | 191 | |
| Cylinder Head/Block Material | Cast Aluminum/Cast Iron | |
| Compression Ratio | 9.6:1 | |
| Net Horsepower @ Engine rpm | 175 @ 5200 | |
| Net Torque (lbsft.) @ Engine rpm | 195 @ 4000 | |
| Recommended Fuel | Unleaded Regular | |
| Fuel Management | Sequential-Port Fuel Injection | |
| Oil Capacity (qts.) | 4 (5 with filter) | |
| EPA Fuel Economy Rating, City/Hwy (Projected) | 20/30 | |

| STEERING | |
|--|-----------------|
| Steering Gear Type | Rack-and-Pinion |
| Overall Ratio | 16.8:1 |
| Number of Wheel Turns (stop-to-stop) | 3.04 |
| Turning Diameter (ft.) (curb-to-curb) | 37.5 |
| Linkage | Rear |
| Tie Rods, Number | 2 |

Century 2000 Special Edition

| TRANSAXLE | |
|---|--|
| Automatic Transmission with Overdrive | |
| Туре | Four-Speed with Electronically Controlled Capacity Clutch |
| Selector Pattern | PRND321 |
| Gear Ratio (each times converter ratio) | |
| First | 2.92 |
| Second | 1.57 |
| Third | 1.00 |
| Fourth | 0.70 |
| Reverse | 2.38 |
| Final Drive Ratio | 3.05 |
| Cooling | Liquid |
| Capacity – Dry (pts.) | 26.8 |

| SUSPENSION | |
|-----------------------|--|
| Front Suspension Type | MacPherson Strut with L-Shaped Lower Control Arm & Aluminum Knuckle |
| Shock Absorbers | Twin-Tube Strut |
| Stabilizer (in.) | 1.18 |
| Rear Suspension Type | Isolated, Independent, Coil Over Strut, Tri-Link Design |
| Shock Absorbers | Twin-Tube Strut |
| Stabilizer (in.) | .55 (Solid) |

| CHASSIS | |
|---------------|---------------------|
| Chassis/Body | Integral Body/Frame |
| Body Material | Steel |

KEY FEATURES

• Powertrain / Chassis / Suspension:

- 3100 SFI V-6 enhancements include increased horsepower and torque, improved exhaust tuning resulting in reduced noise, vibration and harshness
- New electronically controlled four-speed automatic transmission with overdrive
- Power four-wheel, anti-lock disc/drum brakes
- Traction control

• Exterior:

- Two new colors: Gold Metallic and Sterling Silver Metallic
- New, standard 15" chrome-plated, bolt-on wheelcover for Limited
- Daytime running lamps with Twilight Sentinel®
- Remote keyless entry with programmable safety/ security features
- Century 2000 Appearance Package

• Interior:

- Leather seating (standard on Limited) includes seat-mounted, driver-side air bag (new)
- Rear-seat child tether anchors (new)
- Convenience Plus features
- New split fold-down rear seat with storage armrest and dual cup holder (optional)
- Rear-seat heat ducts
- Dual ComforTemp climate control and air-filtration system
- Concert Sound six-speaker system
- PASS-Key® II passive theft-deterrent system
- Retained accessory power (standard on Limited, optional on Custom)
- Inside and driver outside rearview electrochromic mirrors (optional)
- Three-button On Star System (optional)

BRAKES

| Power Brake Type | Power Front Disc/ Rear Drum Anti-Lock System | |
|--|--|--|
| Self-Adjusting Feature | Standard | |
| Hydraulic System Type | Split Diagonal | |
| Effective Area Total (sq. in.) | 98.9 | |
| Gross Lining Area Total (sq. in) | 96.2 | |
| Swept Area Total (sq. in) | 306.8 | |
| Rotor Diameter (in.) (outer) | 7.1/10.8 | |
| Rotor Thickness (in.) | 1.3 | |
| Rotor Material and Type | Cast Iron – Vented | |
| Drum Material and Type | Cast Iron – Finned | |
| Brake Lining Material, Front and Rear | Nonasbestos Semi-Metallic | |
| Front Lining | | |
| Outboard (in.) | 4.96 x 1.81 x .60 | |
| Inboard (in.) | 4.96 x 1.81 x .60 | |
| Rear Lining | | |
| Outboard (in.) | 8.85 x 1.73 x .25 | |
| Inboard (in.) | 8.85 x 1.73 x .25 | |

MODEL AVAILABILITY

Century Custom – Sedan WS69 Century Limited – Sedan WY69

STANDARD FEATURES

Acoustical Insulation Package

| Acoustical Insulation Package |
|--|
| Air Bags – Driver and front passenger (SRS*) (Next Generation) |
| Air Conditioning – Dual ComforTemp climate control |
| Air Filtration System |
| Antenna – Fixed-mast |
| Armrest – Front-seat storage with dual cup holder |
| Assist Handle – Front-seat passenger |
| Battery – 10" Delco Freedom II |
| Brakes – Power four-wheel anti-lock disc/drum |
| Brake, Parking – Push-to-set-and-release |
| Defogger – Front and side window outlets |
| – Electric, rear-window |
| Diagnostics - OBD II |
| |
| Door Locks – Delayed locking |
| Door Locks, Memory – With lock-out protection |
| Door Seals – Triple |
| Drive – Front-wheel |
| Emissions Control – Onboard refueling vapor recovery system |
| Engine – 3100 SFI V-6(increased horsepower and torque) |
| Exhaust – Stainless steel |
| Glass – Soft-Ray [®] side windows |
| – Solar-Ray [®] solar-control windshield and rear window |
| Glove Box – Locking |
| Heat Ducts – Rear seat |
| Hood Release – Inside remote |
| Hood Support Struts – Dual gas cylinder |
| Horn – Dual note |
| Instrumentation - Speedometer, fuel and temperature gauges |
| with trip odometer and warning lights for low fuel, door ajar, trunk ajar, oil level, oil life, coolant level, and washer fluid level |
| |
| Lamps – Daytime running lamps with Twilight Sentinel® |
| Lights – Glove box, trunk, dome |
| Mirrors, Inside Rearview- Map reading lights |
| Mirrors, Inside – Dual covered visor vanity |
| Mirrors, Outside – Dual remote power, folding |
| Moldings – Belt reveal, pillar, roof drip, black door and |
| window frame |
| - Body-color, body-side |
| Multifunctional Control Lever – Turn signals, headlamps high/ low beam, windshield wiper controls and flash-to-pass signal |
| Radio - ETR® AM-FM stereo with seek/scan and clock |
| Remote Keyless Entry |
| Safety Belts – Adjustable shoulder belt comfort guide, driver and front passenger |
| Safety Belts, Front – Lap belt integral with seat, outboard lap/ shoulder belt |
| Safety Belts, Rear – Outboard lap/shoulder belt with comfort guide |
| Seat Adjuster – Two-way manual, driver and front passenger |
| Seats, Front – 55/45 cloth split bench |
| - Seat back recliners, driver and front |
| passenger, manual |
| Seats, Rear – Theater seating |
| |

| Security Locks – Rear door, child |
|--|
| Speakers – Concert Sound II six-speaker system |
| Starter Protection – Starter grind prevention feature, renders starter inoperative while engine is running |
| Steering – Power rack-and-pinion |
| Steering Column – TILT-WHEEL™ adjustable |
| Storage – Front and rear door map pockets |
| Sunshades – Extendible, front |
| Suspension – Four-wheel independent |
| Theft-Deterrent System – PASS-Key® II |
| Tire Inflation Monitor |
| Tires – P205/70R15 all-season blackwall |
| Traction Control |
| Transmission – Electronically controlled four-speed automatic with overdrive |
| Trunk – Full trim |
| – Low lift-over design |
| Wheelcovers – 15" deluxe bolt-on |
| Windows – Power with driver express-down and passenger lock-out features |

Windshield Wipers – Two-speed with variable delay feature

*Supplemental Restraint System

CONVENIENCE PLUS FEATURES

Include electronic reminder tones for ignition key, headlamps, turn signals, parking brake "on" and low fuel; delayed entry and exit lighting; theater dimming; Battery Rundown Protection; lock-out protection; flash-to-pass signal, delayed locking; PASS-Key[®] II passive theft-deterrent system; daytime running lamps with Twilight Sentinel[®] and – on Limited – retained accessory power.

ADDITIONAL LIMITED FEATURES

 Armrest – Rear-seat center

 Carpet Savers – Front and rear

 Leather Seating

 Lights – Courtesy and reading, rear sail panel mounted with passenger assist handles

 Mirrors, Inside – Illuminated dual visor vanity, with extendable sunshades

 Mirrors, Outside – Left and right power remote, folding outside rearview, heated, body-color

 Retained Accessory Power

 Steering – Magnetic variable effort

 Storage – Front seat back pockets

 Whealaurer, Spacific 15" datum abrame helt on

Wheelcovers - Specific 15" deluxe chrome bolt-on

TIRES

Standard, Custom/ Limited P205/70R15

Steel-belted, radial-ply, all-season blackwalls

Optional, Custom/Limited P205/70R15 Steel-belted, radial-ply,

all-season whitewalls

WHEELS

Type and Material Size, Flange; Offset

Standard, Custom Stamped Steel, Bolt-on 15 x 6]; 52mm Standard, Limited

Stamped Steel, Bolt-on 15 x 6J; 52mm Optional, Custom/Limited Cast Aluminum 15 x 6J; 52mm Optional, Custom/Limited Century 2000 Package Cast Aluminum 15 x 6J; 52mm

EXTERIOR COLOR AVAILABILITY

- NEW Gold Metallic
- NEW Sterling Silver Metallic
- Black
- Bordeaux Red Pearl
- Bright White
- Jasper Green Pearl
- Light Sandrift Metallic
- Midnight Blue Pearl
- Twilight Blue Metallic

DIMENSIONS

| Inches unless noted | | Century Custom and Limited Sedans |
|------------------------|---------|--------------------------------------|
| 0 11 | | Eliniaca ocaano |
| Overall: Length | | 194.6 |
| Width | | 72.7 |
| Height | | 56.6 |
| Wheelbase | | 109.0 |
| Front Track | | 62.0 |
| Rear Track | | 61.1 |
| Front Overhang | | 41.6 |
| Rear Overhang | | 44.0 |
| Interior: | | |
| Leg Room (F/R) | | 42.4/36.9 |
| Head Room (F/R) | | 39.4/37.4 |
| Shoulder Room (F/R) | | 58.0/57.1 |
| Hip Room (F/R) | | 54.4/53.3 |
| Interior Volume Index: | | |
| Cu. ft. | | 118.5 |
| Passengers: | | |
| Front | | 3 |
| Rear | | 3 |
| Luggage Capaci | ty: | |
| Cu. ft. | | 16.7 |
| Fuel Tank Capa | acity: | |
| Gal. | | 17.5 |
| Curb Weight: | | |
| Lbs. | Custom | 3,368 |
| | Limited | 3,371 |

CENTURY 2000 SPECIAL EDITION PACKAGE

- Black-out grille with chrome surround
- Century 2000 badging
- Body-color molding and fascia inserts
- · Embroidered headrests and front floor mats
- Specific option content
- Specific 15" wheel